

Tyres for Pantera 7004

Dimensions	Pantera	Pantera-W	Load index	Outer diameter in mm
320/105 R54	X	X	172 D	2040
380/105 R50	X	X	177 D	2052
380/90 R54	X	X	171 D	2054
380/90 R54	X	X	176 D	2050
420/95 R50	X	X	177 D	2052
480/80 R50	X	X	166 D	2050
480/80 R50	X	X	179 D	2050
520/85 R42	X	X	170 D	1956
520/85 R46	X	X	170 D	2052
620/70 R42	X	X	166 D	1935
650/65 R42	X	X	170 D	1945
650/65 R42	X	X	165 D	1936
710/60 R42	X	X	173 E	1885

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required.



Pantera 7004

Technical data: Pantera 7004



Model	Pantera 7004	Pantera 7004-W
Nominal volume (l) / Actual volume (l)	6,600 / 7,000	
Fresh water tank (l)	500	
Boom width (m)	24 – 48	
Pump capacity (l/min)	610	
Max. suction capacity (l/min)	750	
Fuel tank capacity (l)	290 / 400	
DEF tank (l)	20	
Max. working speed (km/h)	20 (30 optional)	
Transport speed (km/h)	up to 50	
Length (m) (Transport position, incl. external wash down kit)	9.77	
Transport width (m)	2.55	2.75
Spraying height min./max. (m) with tyre sizes 380/90 R50	0.35 – 2.75 with lift module 0.35 – 3.45	
Part-width sections min./max. (number)	7 – 13	
No. of sections with individual nozzle switching: AmaSwitch plus or AmaSelect	up to 96	
Unladen weight (kg)	approx. 12.000 kg depending on the level of equipment	
Max. total weight (kg)	20,000	
Turning circle, all-wheel steer (m)	4.50	
Track width (m) with tyre sizes 380/90 R50 (offset + 50 mm)	2.00 (1.85)* - 2.75	2.25 – 3.00
Ground clearance (m) with tyre sizes 380/90 R50	1.30	
Engine power (emission standard 3A / emission standard 5)	max. 200 kW (272 hp) / 225 kW (306 hp)	

*with tyre size 380/90 R54

Illustrations, content and technical data are not binding and may differ depending on the level of equipment. Country-specific road traffic regulations apply and must be complied with, meaning that special approval may be required.